

Portable PPM Oxygen Meter –OMPM-B

SPECIFICATIONS :

- ◆ Range : 0 to 1999 PPM
- ◆ Resolution 1 PPM

- ◆ Range : 0 to 25.% (for Air calibration)
- ◆ Operating Temp : 10 °C to 45 °C

- ◆ Display : 3 ½ digit LCD
- ◆ Sensor Type : Electro chemical
- ◆ Cell by-pass valve to isolate (Cell when not in use.)

- ◆ Inlet Outlet Fitting : 1/8" Compression
- ◆ Sensor Life 12 Month

- ◆ Power Supply : 9 V dry cell battery (Rechargeable batteries optional)
Low Battery Low Battery indication

- Operating Keys Span adjustment pot & On- Off & Range selector switch

- ◆ Weight: 300 Gms. App.
- ◆ Accessories ; carrying case with belt

Model –OMPM-B



APPLICATIONS

- Gas impurity check
- Cryogenics.
- Chemical Engineering
- N2 Plant, Ar .Plant
- Quality Assurance

SPECIAL FEATURES

- Small & Light weight
- Fast Response
- Easy to read Display
- Hand held instrument
- Low Battery Indicator
- Accurate, disposable Electromical Sensor

- ◆ In the interest of continued product we reserve the right to change the specification without prior notice

Hemaki
LAB-SERVICES

252-D Amar Gian Industrial Estate, L.B.S. Marg, Khopat, Thane (W) 400 6
Maharashtra, India Tel. +91 (022) 2547 49 01 Telefax : 2547 58 68
Email : hemaki@vsnl.com Web site : www.hemaki.com